

HOLLOW WALL ANCHORS

HOLLOW WALL ANCHORS

FEATURES

- Flush Finish, low profile head
- Anit Rotation barbs in head flange
- Collapsing legs with integral nut, Provides high strength and allows the screw removal without the loss of the anchor within the cavity
- Can be set with a setting tool for speed of assembly or power screwdrive



MATERIALS


Carbon Steel

APPLICATIONS


Electrical fittings, pipe saddles, cupboard shelves, consumer appliances, wall shelves, brackets.




INSTALLATION



1. Drill the correct size hole through the material then tap the hollow wall anchor into the hole until it is flush with the surface.



2. Turn the screw with a suitable screwdriver to expand the anchor



3. Remove the screw and place through the hole in the fixture and back into the hollow wall anchor and tighten the screw.

ANCHOR DETAILS

Anchor Size	Anchor Length (mm)	Hole Diameter Φ (mm)	Gypsum Thickness (mm)	Weight Loading (kgs)	Packed Quantity (Box, Carton)	Part No. Carbon Steel (Plate)
M4 (409)	40	8	4 to 9	40-60	100 , 1000	HAZP40900
M4 (416)	47	8	9 to 16	40-60	100 , 1000	HAZP41600



SETTING TOOLS DETAILS

Description	Packed Quantity (Box, Carton)	Part No.
Hollow Wall Setting Tool	1, 30	STT-WHA

Description	Packed Quantity (Box, Carton)	Part No.
SET Hollow Wall Anchor and Setting Tool	1	KITHA0081
• Hollow Wall Anchor #409	40 PCS	
• Hollow Wall Anchor #416	40 PCS	
• Hollow Wall Setting Tool	1 PCS	

